

SCM415・435

機械構造用合金鋼鋼管

寸法 (mm)		SCM	SCM
外径	肉厚	415	435

27.2	2.8	○	
	3.2	○	
	4.0	○	○
	4.5	○	
31.8	3.2		○
	3.5	○	○
	4.0	○	○
	5.0	○	
	5.5	○	
	6.0	○	
34.0	3.2	◎	○
	3.5	○	◎
	4.0	○	○
	4.5	◎	◎
	5.0	○	○
	5.5	◎	◎
	6.0	◎	○
	7.0	◎	○
38.1	3.5	○	○
	4.0	○	◎
	4.5	○	
	5.0	○	○
	5.5	○	
	6.0		◎
	6.5	○	
	7.0		○
42.7	3.2	○	○
	4.0	◎	◎
	4.5		○
	5.0	◎	◎
	5.5	○	
	6.0	◎	◎
	6.5	○	
	7.0	◎	◎
	7.5		○
	8.0	◎	◎
	10.0		○
	12.0		○

寸法 (mm)		SCM	SCM
外径	肉厚	415	435

45.0	4.5		○
	5.5		○
	6.5		○
	7.5		○
48.6	4.0	○	○
	4.5	○	
	5.0	○	◎
	6.0		◎
	7.0	◎	○
	8.0	○	◎
	8.5		○
	10.0		○
50.8	4.5		○
	5.0		○
	6.0	○	
	6.5		
	7.0		○
	8.0	○	○
	10.0		○
	12.0		○
54.0	6.0		○
	7.0		○
	8.0	○	○
	9.0		○
	10.0	○	○
	12.0		○
57.0	7.0	◎	○
	8.0	○	◎
	10.0	○	○
	12.0		○
60.5	6.0	○	○
	7.0		○
	8.0	○	○
	10.0	○	
	11.0		
	12.0	○	○
15.0		○	

寸法 (mm)		SCM	SCM
外径	肉厚	415	435

63.5	8.0	○	○
	9.0		○
	10.0		○
	12.0	○	○
	15.0		○
65.0	8.0	○	
	9.0	○	
	12.0	○	
70.0	6.0		○
	8.0		○
	10.0	○	○
	12.0	○	○
73.0	8.0	○	
	10.0	○	○
	12.0	○	○
	14.0		
76.3	15.0		○
	7.0		○
	8.0	○	○
	10.0	○	○
78.5	12.0	○	○
	14.0		
	15.0		○
82.6	7.75	○	
	10.5	○	
	12.0		○
85.0	15.0		○
	18.0		○
	89.1	10.0	
89.1	11.0	○	
	12.0		○
	14.0		○
	18.0		○
93.0	20.0		
	27.0		○
	95.0	10.0	
95.0	12.0	○	
	97.0	10.0	○

寸法 (mm)		SCM	SCM
外径	肉厚	415	435

101.6	10.0		○
	12.0		○
	15.0	○	○
	20.0		○
103.0	12.0	○	
105.0	12.0		○
	18.0		○
107.0	10.0	○	
110.0	12.0		○
114.3	8.0		○
	12.0		○
	15.0	○	○
	20.0		○
	25.0		○
118.0	11.0	○	
120.0	12.0	◎	○
	20.0	○	
127.0	10.5	○	
	15.0		○
	20.0		◎
135.0	12.0		◎
	15.0	○	
	20.0		○
139.8	12.0		○
146.0	15.0		○
	152.4	8.0	
152.4	12.0		○
	156.0	18.0	○
165.2	19.6	○	
177.8	21.0	○	
180.0	18.0	○	
185.0	20.0	○	
193.7	10.0		○
	19.0	○	
205.0	20.5	○	
216.3	21.0	○	
241.8	24.0	○	
267.4	26.5	○	

◎ 常備材

○ 非常備材

△ 取扱材