

STK400・490

一般構造用炭素鋼鋼管

寸 法		重量	在庫
Φ	T	kg/m	400

21.7	1.9	0.928	◎
	2.3	1.10	○
	2.8	1.31	△
27.2	1.9	1.19	◎
	2.3	1.68	◎
	2.8	1.31	○
34.0	3.9	2.24	△
	2.3	1.80	◎
	3.2	2.43	◎
42.7	2.3	2.29	◎
	3.2	3.12	◎
	3.5	3.38	◎
48.6	2.3	2.63	◎
	2.8	3.16	○
	3.2	3.58	◎
	3.5	3.89	◎
	5.1	5.47	○
60.5	2.3	3.30	◎
	2.8	3.98	◎
	3.2	4.52	◎
	3.8	5.31	◎
	4.9	6.72	○
76.3	5.5	7.46	△
	2.8	5.08	◎
	3.2	5.77	◎
	4.2	7.47	◎
	5.2	9.12	○
89.1	6.0	10.4	△
	7.0	12.0	○
	2.8	5.96	◎
	3.2	6.78	◎
	4.2	8.79	◎
101.6	5.5	11.3	◎
	7.6	15.3	△
	3.2	7.76	◎
	3.5	8.46	△
	4.2	10.1	◎
114.3	5.5	13.0	△
	5.7	13.5	◎
	8.1	18.7	△
	3.5	9.56	◎
	4.5	12.2	◎
127.0	6.0	16.0	◎
	8.6	22.4	△
	4.5	13.6	◎

寸 法		重量	在 庫	
Φ	T	kg/m	400	490

139.8	3.5	11.8	◎	
	4.0	13.4	◎	
	4.5	15.0	◎	△
	6.0	19.8	◎	
	6.6	21.7	◎	△
	8.1	26.3	○	
	9.3	29.9	○	
	11.0	34.9	△	
	5.0	18.2	◎	
	3.5	34.9	○	
152.4	3.7	14.7	◎	
	4.5	17.8	◎	
	5.0	19.8	◎	△
	6.0	23.6	○	
	7.1	27.7	◎	△
	9.3	35.8	○	
	10.3	39.3	△	
	4.5	20.7		
	5.3	24.2	◎	△
	6.0	27.3	○	
165.2	7.0	31.7	◎	
	11.0	48.7	△	
	4.5	23.5	◎	
	5.8	30.1	◎	△
	7.0	36.1	○	
	8.2	42.1	◎	△
	10.3	52.3	○	
	12.7	63.8	◎	△
	15.1	74.9	△	
	6.2	36.0	◎	
190.7	4.5	37.4	○	
	5.8	37.4	◎	
	6.0	38.7	○	
	6.6	42.4	◎	△
	8.0	51.2	○	
	9.3	59.2	◎	△
	12.7	79.8	◎	△
	15.1	93.9	△	
	6.0	46.2	◎	
	6.4	49.2	◎	
216.3	6.9	53.0	◎	△
	7.9	60.5	◎	
	9.0	68.7	△	
	9.5	72.4	◎	
	241.8	6.2	36.0	◎
	267.4	4.5	37.4	○
		5.8	37.4	◎
		6.0	38.7	○
		6.6	42.4	◎
		8.0	51.2	○
241.8	9.3	59.2	◎	△
	12.7	79.8	◎	△
	15.1	93.9	△	
	6.0	46.2	◎	
	6.4	49.2	◎	
	6.9	53.0	◎	△
	7.9	60.5	◎	
	9.0	68.7	△	
	9.5	72.4	◎	
	318.5	6.0	46.2	◎
267.4	6.4	49.2	◎	
	6.9	53.0	◎	△
	7.9	60.5	◎	
	9.0	68.7	△	
	9.5	72.4	◎	
	318.5	6.0	46.2	◎
	6.4	49.2	◎	
	6.9	53.0	◎	△
	7.9	60.5	◎	
	9.0	68.7	△	

寸 法		重量	在 庫	
Φ	T	kg/m	400	490

318.5	10.3	78.3	◎	△
	12.7	95.8	◎	△
	14.3	107	○	
	17.4	129	△	
355.6	6.4	55.1	◎	
	7.9	67.7	◎	
	9.5	81.1	◎	△
	11.1	94.3	◎	
	12.7	107	◎	△
	15.1	127	○	△
	19.0	158	△	
	6.0	59.2	○	
406.4	6.4	63.1	◎	
	7.9	77.6	◎	
	9.0	88.2	○	
	9.5	93.0	◎	△
	12.7	123	◎	△
	16.0	154	◎	△
	19.0	182	◎	△
	6.4	71.1	◎	
457.2	7.9	87.5	◎	
	9.5	105	◎	
	12.7	139	◎	
	14.3	156	○	
	16.0	174	◎	
	19.0	205	◎	
	22.0	236	△	
	6.4	79.2	◎	
508.0	7.9	97.4	◎	
	9.5	117	◎	
	12.7	155	◎	△
	15.1	184	○	
	16.0	194	◎	△
	19.0	229	◎	△
	20.6	248	○	
	22.0	264	△	△
558.8	6.4	87.2	◎	
	7.9	107	◎	
	9.5	129	◎	
	12.7	171	◎	
	16.0	214	◎	
	19.0	253	○	
	22.0	291	△	
	6.4	95.2	◎	
609.6	7.9	117	◎	

寸 法		重量	在 庫	
Φ	T	kg/m	400	490

609.6	9.5	141	◎	
	12.7	187	◎	△
	16.0	234	◎	△
	19.0	277	◎	△
	22.0	291	△	△
660.4	6.4	103	◎	
	7.9	127	◎	
	9.5	152	◎	
	12.7	203	◎	
	16.0	254	○	
	19.0	301	△	
711.2	6.4	111	◎	
	7.9	137	◎	
	9.5	164	◎	
	12.7	219	◎	
	16.0	274	◎	
	19.0	324	△	
	22.0	374	△	
	6.4	119	○	
762.0	7.9	147	◎	
	9.5	176	◎	
	12.7	235	◎	
	16.0	294	○	
	6.4	127	○	
812.8	7.9	157	○	
	8.0	159	◎	
	9.5	188	◎	
	12.7	250	○	
	16.0	314	○	
	19.0	372	△	
	12.7	266	◎	
	7.9	177	◎	
863.6	8.0	179	◎	
	9.5	212	◎	
	12.7	282	◎	
	16.0	354	◎	
	7.9	196	◎	
914.4	9.5	236	◎	
	12.7	314	◎	
	16.0	395	◎	
1016.0	9.5	260	△	
	10.3	281	△	
	9.5	283	◎	
1117.6	12.7	378	◎	
	16.0	475	◎	

◎常備材 ○非常備材 △取扱材