STPG370 S-H

圧力配管用炭素鋼鋼管 継目無

呼び径		外径								呼び	厚さ							
			Sch.10		Sch.20		Sch.30		Sch.40		Sch.60		Sch.80		Sch.100		Sch.120	
(A)	(B)	mm	厚さ	在庫	厚さ	在庫	厚さ	在庫										
6	1/8	10.5							1.7	0	2.2		2.4	0				
8	1/4	13.8							2.2	0	2.4		3.0	0				
10	3/8	17.3							2.3	0	2.8	0	3.2	0				
15	1/2	21.7							2.8	0	3.2	0	3.7	0				
20	3/4	27.2							2.9	0	3.4	0	3.9	0				
25	1	34.0							3.4	0	3.9	0	4.5	0				
32	1 1/4	42.7							3.6	0	4.5	0	4.9	0				
40	1 1/2	48.6							3.7	0	4.5	0	5.1	0				
50	2	60.5			3.2	0			3.9	0	4.9	0	5.5	0				
65	2 1/2	76.3			4.5	0			5.2	0	6.0	0	7.0	0				
80	3	89.1			4.5	0			5.5	0	6.6	0	7.5	0				
90	3 1/2	101.6			4.5	0			5.7	0	7.0	0	8.1	0				
100	4	114.3			4.9	0			6.0	0	7.1	0	8.5	0			11.1	
125	5	139.8			5.1	0			6.6	0	8.1	0	9.5	0			12.7	
150	6	165.2			5.5	0			7.1	0	9.3	0	11.0	0			14.3	
200	8	216.3			6.4	0	7.0	0	8.2	0	10.3	0	12.7	0	15.1		18.2	
250	10	267.4			6.4	0	7.8	0	9.3	0	12.7	0	15.1	0	18.2		21.4	
300	12	318.5			6.4	0	8.4	0	10.3	0	14.3	0	17.4	0	21.4		25.4	
350	14	355.6	6.4		7.9	0	9.5	0	11.1	0	15.1	0	19.0	0	23.8		27.8	
400	16	406.4	6.4		7.9	0	9.5	0	12.7	0	16.7	0	21.4	0	26.2		30.9	
450	18	457.2	6.4		7.9		11.1		14.3		19.0		23.8		29.4		34.9	
500	20	508.0	6.4		9.5		12.7		15.1		20.6		25.2		32.5		38.1	
600	24	609.6	6.4		9.5		14.3		17.5		24.6		31.0		38.9		46.0	

6A、8A、10A(S-C) 15A(S-C、S-H)

◎ 常備材 ○ 非常備材

△ 取扱材