

STPL380

低温配管用鋼管

呼び径		外径	呼び厚さ																			
			S/20		S/30		S/40		S/60		S/80		S/100		S/120		S/140		S/160		XXS	
(A)	(B)	mm	肉厚	在庫	肉厚	在庫	肉厚	在庫	肉厚	在庫	肉厚	在庫	肉厚	在庫	肉厚	在庫	肉厚	在庫	肉厚	在庫	肉厚	在庫
6	1/8	10.5					1.7	△			2.4	△										
8	1/4	13.8					2.2	△			3.0	△										
10	3/8	17.3					2.3	△			3.2	△										
15	1/2	21.7					2.8	○			3.7	◎							4.7	◎	7.5	△
20	3/4	27.2					2.9	◎			3.9	◎							5.5	◎	7.8	△
25	1	34.0					3.4	△			4.5	◎							6.4	○	9.1	△
32	1 1/4	42.7					3.6	◎			4.9	△							6.4	◎	9.7	△
40	1 1/2	48.6					3.7	△			5.1	◎							7.1	◎	10.2	△
50	2	60.5					3.9	◎			5.5	◎							8.7	◎	11.1	△
65	2 1/2	76.3					5.2	△			7.0	△							9.5	○	14.0	△
80	3	89.1					5.5	◎			7.6	◎							11.1	○	15.2	△
90	3 1/2	101.6					5.7	◎			8.1	◎							12.7	△		
100	4	114.3					6.0	◎			8.6	○			11.1	△			13.5	△	17.1	△
125	5	139.8					6.6	◎			9.5	○			12.7	△			15.9	△	19.1	△
150	6	165.2					7.1	◎			11.0	△			14.3	△			18.2	△	21.9	△
200	8	216.3	6.4	△	7.0	△	8.2	△	10.3	△	12.7	○	15.1	△	18.2	△	20.6	△	23.0	△	22.2	△
250	10	267.4	6.4	△	7.8	△	9.3	△	12.7	△	15.1	△	18.2	△	21.4	△	25.4	△	28.6	△	25.4	△
300	12	318.5	6.4	△	8.4	△	10.3	△	14.3	△	17.4	△	21.4	△	25.4	△	28.6	△	33.3	△		
350	14	355.6	7.9	△	9.5	△	11.1	△	15.1	△	19.0	△	23.8	△	27.8	△	31.8	△	35.7	△		
400	16	406.4	7.9	△	9.5	△	12.7	△	16.7	△	21.4	△	26.2	△	30.9	△	36.5	△	40.5	△		
450	18	457.2	7.9	△	11.1	△	14.3	△	19.0	△	23.8	△							45.2	△		
500	20	508.0	9.5	△	12.7	△			20.6	△												

(要確認)

◎ 常備材

○ 品薄材

△ 取扱材