

# STPT370 S-H

高温配管用炭素鋼鋼管

呼び径		外径	呼び厚さ															
			Sch.40		Sch.60		Sch.80		Sch.100		Sch.120		Sch.140		Sch.160		XXS	
(A)	(B)	mm	厚さ	在庫	厚さ	在庫	厚さ	在庫	厚さ	在庫	厚さ	在庫	厚さ	在庫	厚さ	在庫	厚さ	在庫
6	1/8	10.5	1.7	◎	2.2		2.4	◎										
8	1/4	13.8	2.2	◎	2.4		3.0	◎										
10	3/8	17.3	2.3	◎	2.8		3.2	◎										
15	1/2	21.7	2.8	◎	3.2		3.7	◎							4.7	◎	7.5	◎
20	3/4	27.2	2.9	◎	3.4		3.9	◎							5.5	◎	7.8	◎
25	1	34.0	3.4	◎	3.9		4.5	◎							6.4	◎	9.1	◎
32	1 1/4	42.7	3.6	◎	4.5		4.9	◎							6.4	◎	9.7	◎
40	1 1/2	48.6	3.7	◎	4.5		5.1	◎							7.1	◎	10.2	◎
50	2	60.5	3.9	◎	4.9		5.5	◎							8.7	◎	11.1	◎
65	2 1/2	76.3	5.2	◎	6.0		7.0	◎							9.5	◎	14.0	◎
80	3	89.1	5.5	◎	6.6		7.6	◎							11.1	◎	15.2	◎
90	3 1/2	101.6	5.7	◎	7.0		8.1	◎							12.7	◎		
100	4	114.3	6.0	◎	7.1		8.6	◎			11.1	◎			13.5	◎	17.1	◎
125	5	139.8	6.6	◎	8.1		9.5	◎			12.7	◎			15.9	◎	19.1	◎
150	6	165.2	7.1	◎	9.3		11.0	◎			14.3	◎			18.2	◎	21.9	◎
200	8	216.3	8.2	◎	10.3		12.7	◎	15.1	◎	18.2	◎	20.6	◎	23.0	◎	22.2	
250	10	267.4	9.3	◎	12.7		15.1	◎	18.2	◎	21.4	◎	25.4	◎	28.6	◎		
300	12	318.5	10.3	◎	14.3		17.4	◎	21.4	◎	25.4	◎	28.6	◎	33.3	◎		
350	14	355.6	11.1	◎	15.1		19.0	◎	23.8	◎	27.8	◎	31.8	◎	35.7	◎		
400	16	406.4	12.7	◎	16.7		21.4	◎	26.2	◎	30.9	◎	26.5	◎	40.5	◎		
450	18	457.2	14.3		19.0		23.8		29.4		34.9		39.7		45.2			
500	20	508.0	15.1		20.6		26.2		32.5		38.1		44.4		50.0			
600	24	609.6	17.5		24.6		31.0		38.9		46.0		52.4		59.5			

6A、8A、10A(S-C) 15A(S-C、S-H)

◎ 常備材      ○ 非常備材      △ 取扱材

# STPT410 S-H

高温配管用炭素鋼鋼管

呼び径		外径	呼び厚さ															
			Sch.40		Sch.60		Sch.80		Sch.100		Sch.120		Sch.140		Sch.160		XXS	
(A)	(B)	mm	厚さ	在庫	厚さ	在庫	厚さ	在庫	厚さ	在庫	厚さ	在庫	厚さ	在庫	厚さ	在庫	厚さ	在庫
6	1/8	10.5	1.7		2.2		2.4											
8	1/4	13.8	2.2		2.4		3.0	○										
10	3/8	17.3	2.3	○	2.8		3.2	○										
15	1/2	21.7	2.8	○	3.2		3.7	○							4.7	○	7.5	○
20	3/4	27.2	2.9	○	3.4		3.9	○							5.5	○	7.8	○
25	1	34.0	3.4	○	3.9		4.5	○							6.4	○	9.1	○
32	1 1/4	42.7	3.6	○	4.5		4.9	○							6.4	○	9.7	○
40	1 1/2	48.6	3.7	○	4.5		5.1	○							7.1	○	10.2	○
50	2	60.5	3.9	○	4.9		5.5	○							8.7	○	11.1	○
65	2 1/2	76.3	5.2	○	6.0		7.0	○							9.5	○	14.0	○
80	3	89.1	5.5	○	6.6		7.6	○							11.1	○	15.2	
90	3 1/2	101.6	5.7	○	7.0		8.1	○							12.7	○		
100	4	114.3	6.0	○	7.1		8.6	○			11.1				13.5	○	17.1	
125	5	139.8	6.6	○	8.1		9.5	○			12.7				15.9	○	19.1	
150	6	165.2	7.1	○	9.3		11.0	○			14.3				18.2	○	21.9	
200	8	216.3	8.2	○	10.3		12.7	○	15.1		18.2		20.6		23.0	○	22.2	
250	10	267.4	9.3	○	12.7		15.1	○	18.2		21.4		25.4		28.6	○		
300	12	318.5	10.3	△	14.3		17.4	△	21.4		25.4		28.6		33.3	◎		
350	14	355.6	11.1	△	15.1		19.0	△	23.8		27.8		31.8		35.7			
400	16	406.4	12.7	△	16.7		21.4	△	26.2		30.9		26.5		40.5			
450	18	457.2	14.3		19.0		23.8		29.4		34.9		39.7		45.2			
500	20	508.0	15.1		20.6		26.2		32.5		38.1		44.4		50.0			
600	24	609.6	17.5		24.6		31.0		38.9		46.0		52.4		59.5			

6A、8A、10A(S-C) 15A(S-C、S-H)

◎ 常備材      ○ 非常備材      △ 取扱材