

# OST-2

## 油圧配管用精密炭素鋼鋼管

外径	肉厚	長さ	在庫
mm	mm	mm	

4.0	1.0	4,000	◎
	1.2	4,000	
	1.5	4,000	
6.0	1.0	4,000	◎
	1.2	4000	
	1.5	4,000	◎
	2.0	4,000	◎
8.0	1.0	4,000	◎
	1.2	4,000	◎
	1.5	4,000	◎
	2.0	4,000	◎
	2.5	4,000	
9.5	1.5	4,000	◎
10.0	1.0	4,000	◎
	1.2	4,000	◎
	1.5	4,000	◎
	2.0	4,000	◎
	2.5	4,000	◎
10.5	1.7	5,500	
	2.2	5,500	◎
12.0	1.0	4,000	◎
	1.2	4,000	◎
	1.5	4,000	◎
	1.5	5,500	◎
	2.0	4,000	◎
	2.5	4,000	◎
13.8	2.2	5,500	◎
	2.4	4,000	◎
	3.0	5,500	◎
14.0	1.0	4,000	◎
15.0	1.0	4,000	◎
	1.2	4,000	◎
	1.5	4,000	◎
	2.0	4,000	◎
	2.0	5,500	◎
	2.5	4,000	◎
	3.0	4,000	◎

外径	肉厚	長さ	在庫
mm	mm	mm	

16.0	1.2	4,000	◎
	1.5	4,000	◎
	2.0	4,000	◎
	2.5	4,000	◎
	3.0	4,000	◎
17.3	2.3	5,500	◎
	2.8	4,000	◎
	3.2	5,500	◎
18.0	1.5	4,000	◎
	2.0	4,000	◎
	2.5	4,000	◎
	3.0	4,000	◎
19.0	2.0	4,000	◎
20.0	1.5	4,000	◎
	2.0	4,000	◎
	2.5	4,000	◎
	3.0	4,000	◎
	3.5	4,000	◎
21.7	2.0	5,500	◎
	2.8	5,500	◎
	3.2	4,000	◎
	3.2	5,500	◎
	3.7	5,500	◎
22.0	4.7	5,500	
	1.2	4,000	◎
	1.5	4,000	◎
	2.0	4,000	◎
	2.5	4,000	◎
	3.0	4,000	◎
25.0	4.0	4,000	
	1.5	4,000	
25.0	2.0	4,000	◎
	2.5	4,000	◎
	3.0	4,000	◎
	3.5	4,000	◎
	3.5	4,000	◎
	3.5	4,000	

外径	肉厚	長さ	在庫
mm	mm	mm	

27.2	2.9	5,500	
	3.2	5,500	◎
	3.2	6,000	◎
	3.4	4,000	◎
	3.9	5,500	◎
28.0	2.0	4,000	◎
	2.5	4,000	◎
	3.0	4,000	◎
	3.5	4,000	◎
	4.0	4,000	◎
30.0	5.0	4,000	◎
	2.0	4,000	◎
	2.5	4,000	◎
	3.0	4,000	◎
	3.5	4,000	◎
	4.0	4,000	◎
34.0	4.0	4,500	◎
	5.0	4,000	◎
	3.2	5,500	◎
	3.9	4,000	◎
	4.0	4,900	◎
	4.0	5,000	◎
	4.0	5,300	◎
35.0	4.5	5500	◎
	2.5	4,000	◎
	3.0	4,000	◎
	3.5	4,000	◎
42.0	4.0	4,000	◎
	3.0	4,000	◎
	4.0	4,000	◎
42.7	4.5	4,000	◎

◎ 常備材  
○ 非常備材  
△ 取扱材