

# S45C

## 機械構造用高炭素鋼鋼管

外径 (mm)	肉厚 (mm)	在庫
21.7	4.0	△
	5.0	△
	6.0	△
	7.0	△
25.4	2.3	△
	2.8	
	3.2	△
	3.5	○
	4.0	◎
	4.5	◎
	5.0	◎
	6.0	◎
27.2	2.8	○
	3.2	○
	3.5	○
	4.0	◎
	4.5	◎
	5.0	◎
	5.5	○
	6.0	◎
30.0	4.0	◎
	5.0	◎
	6.0	◎
	7.0	◎
	8.0	◎
31.8	3.2	△
	3.5	○
	4.0	◎
	4.5	○
	5.0	◎

外径 (mm)	肉厚 (mm)	在庫
31.8	5.5	△
	6.0	◎
	7.0	◎
	8.0	◎
	9.0	△
34.0	3.2	◎
	3.5	◎
	4.0	◎
	4.5	◎
	5.0	◎
	5.5	○
	6.0	◎
	6.4	◎
	7.0	◎
	8.0	◎
38.1	3.2	△
	3.5	△
	4.0	◎
	4.5	◎
	5.0	◎
	5.5	△
	6.0	◎
	7.0	◎
	8.0	◎
	9.0	◎
40.0	9.5	
	10.0	◎
	5.0	◎
40.0	6.0	◎
	7.0	◎
	8.0	◎
	8.0	◎

外径 (mm)	肉厚 (mm)	在庫
40.0	9.0	◎
	10.0	◎
42.7	3.2	○
	3.5	◎
	4.0	◎
	4.5	◎
	5.0	◎
	5.5	△
	6.0	◎
	6.4	
	7.0	◎
	8.0	◎
	8.5	◎
	10.0	◎
45.0	12.0	◎
	15.0	
	4.0	◎
	4.5	◎
	5.0	◎
	6.0	◎
	7.0	◎
48.6	8.0	◎
	9.0	◎
	10.0	◎
	11.0	△
	12.0	◎
	15.0	○
	3.5	△
48.6	4.0	◎
	4.5	
	5.0	◎
	5.5	△
	6.0	◎

◎ 常備材  
○ 非常備材  
△ 取扱材

# S45C 機械構造用高炭素鋼鋼管

外径 (mm)	肉厚 (mm)	在庫
48.6	7.0	◎
	8.0	◎
	9.0	◎
	10.0	◎
	12.0	◎
	15.0	◎
50.8	3.5	○
	4.0	△
	5.0	◎
	6.0	◎
	6.5	○
	7.0	◎
	8.0	◎
	8.5	
	9.0	△
	10.0	◎
	12.0	◎
	14.0	○
	15.0	◎
54.0	4.0	◎
	5.0	○
	6.0	◎
	7.0	◎
	7.5	
	8.0	◎
	10.0	◎
	12.0	◎
	14.0	△
	15.0	◎
	18.0	◎

外径 (mm)	肉厚 (mm)	在庫
57.0	4.0	
	4.5	
	5.0	◎
	5.5	
	6.0	◎
	7.0	◎
	8.0	◎
	9.0	○
	10.0	◎
	12.0	◎
	15.0	◎
60.5	4.0	◎
	5.0	◎
	6.0	◎
	6.5	△
	7.0	◎
	8.0	◎
	9.0	○
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
62.0	7.0	△
63.5	4.0	
	4.5	△
	5.0	△
	6.0	◎
	7.0	◎
	8.0	◎
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	△

外径 (mm)	肉厚 (mm)	在庫
65.0	5.0	◎
	6.0	◎
	7.0	◎
	8.0	◎
	9.0	△
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	△
68.0	8.0	◎
	10.0	◎
	12.0	◎
	15.0	◎
	15.5	△
70.0	5.0	◎
	6.0	◎
	7.0	◎
	8.0	◎
	9.0	△
	10.0	◎
	11.0	○
	12.0	◎
	13.0	○
	15.0	◎
20.0	◎	
72.0	10.0	△
73.0	5.0	
	6.0	△
	7.0	○
	8.0	◎
	10.0	◎
	12.0	◎
	13.0	△
15.0	◎	

◎ 常備材  
○ 非常備材  
△ 取扱材

# S45C 機械構造用高炭素鋼鋼管

外径 (mm)	肉厚 (mm)	在庫
73.0	16.0	◎
	17.0	△
	18.0	◎
	20.0	◎
	25.0	◎
76.3	5.0	◎
	6.0	◎
	7.0	◎
	8.0	◎
	9.0	
	10.0	◎
	12.0	◎
	13.0	○
	14.5	
	15.0	◎
	17.0	
	18.0	◎
	20.0	◎
	25.0	◎
77.0	7.0	△
80.0	6.0	
	7.0	
	8.0	◎
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	25.0	○
82.6	6.0	◎
	7.0	△
	8.0	◎
	9.0	
	10.0	◎
	12.0	◎
	13.0	
	15.0	◎
18.0	◎	

外径 (mm)	肉厚 (mm)	在庫	
82.6	20.0	◎	
	22.0	◎	
	25.0	◎	
	30.0		
83.5	15.0		
85.0	7.5		
	8.0	◎	
	10.0	◎	
	12.0	◎	
	15.0	◎	
	18.0	◎	
	20.0	◎	
	24.0		
	25.0	◎	
30.0			
87.0	7.5		
	10.0		
89.1	7.0	△	
	8.0	◎	
	9.0		
	10.0	◎	
	11.0	△	
	11.1		
	12.0	◎	
	14.0		
	15.0	◎	
18.0	◎		
92.5	18.5		
	20.0	◎	
	22.0	○	
	25.0	◎	
	30.0		
	92.5	13.0	
	93.0	11.0	
		16.0	
16.9			
18.0			
23.0			

外径 (mm)	肉厚 (mm)	在庫
95.0	8.0	◎
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	22.5	○
	25.0	◎
96.0	8.0	○
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	○
	20.0	◎
	22.5	△
	25.0	◎
30.0	○	
97.0	10.5	△
101.6	8.0	◎
	9.0	△
	10.0	◎
	12.0	◎
	13.0	
	13.5	
	15.0	◎
	18.0	◎
	20.0	◎
22.0	△	
102.5	23.0	○
	25.0	◎
	30.0	◎
	35.0	◎
	12.0	
	13.0	
102.5	16.0	
	18.0	

◎ 常備材  
○ 非常備材  
△ 取扱材

# S45C

## 機械構造用高炭素鋼鋼管

外径 (mm)	肉厚 (mm)	在庫
105.0	5.0	
	8.0	△
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	○
108.0	8.0	
	10.5	
	11.0	
	15.0	
	16.5	
110.0	5.0	△
	8.0	○
	10.0	◎
	12.0	◎
	15.0	◎
	16.0	
	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
35.0	◎	
114.3	4.5	
	7.0	○
	8.0	◎
	10.0	◎
	12.0	◎
	13.5	◎
	14.0	
	15.0	◎
	16.0	△

外径 (mm)	肉厚 (mm)	在庫
114.3	18.0	◎
	20.0	◎
	22.0	○
	25.0	◎
	30.0	◎
	35.0	◎
118.0	10.5	
	11.0	
	13.5	
	16.0	
120.0	8.0	◎
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	25.0	◎
	35.0	◎
123.0	8.5	
	11.0	
	16.0	
124.0	14.0	
127.0	7.0	
	8.0	◎
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
35.0	◎	
40.0		

外径 (mm)	肉厚 (mm)	在庫
130.0	6.0	◎
	8.0	◎
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
40.0	◎	
133.0	16.0	
135.0	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
35.0	◎	
138.0	16.0	
	18.5	
139.8	4.5	
	7.0	○
	8.0	◎
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	22.0	○
25.0	◎	
28.0		

◎ 常備材  
○ 非常備材  
△ 取扱材

# S45C 機械構造用高炭素鋼鋼管

外径 (mm)	肉厚 (mm)	在庫
139.8	30.0	◎
	35.0	◎
	40.0	◎
	43.0	
145.0	15.0	
146.0	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	18.5	
	20.0	◎
	22.0	○
	23.0	
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	152.4	8.0
10.0		◎
12.0		◎
13.0		◎
15.0		◎
16.0		
18.0		◎
18.5		
19.0		
20.0		◎
22.0		
25.0		◎
30.0		◎
32.5		
34.0		
35.0		◎
40.0		◎
45.0	◎	

外径 (mm)	肉厚 (mm)	在庫
159.0	8.0	
	9.0	
	10.0	◎
	12.0	◎
	15.0	◎
	16.5	
	18.0	◎
	20.0	◎
	23.0	△
	25.0	◎
	27.0	
	28.0	
	30.0	◎
	33.0	
165.2	6.0	
	10.0	◎
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
	33.0	
	35.0	◎
	38.0	
40.0	◎	
45.0	◎	
50.0		

外径 (mm)	肉厚 (mm)	在庫
168.3	10.0	◎
	15.0	◎
	16.0	△
	18.0	◎
	20.0	◎
	23.0	△
	25.0	◎
	30.0	◎
	35.0	◎
	38.0	○
	40.0	◎
177.8	10.0	◎
	11.0	○
	12.0	◎
	15.0	◎
	16.0	○
	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
180.0	25.0	◎
	30.0	○
	35.0	◎
185.0	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
45.0	△	
50.0		

◎ 常備材  
○ 非常備材  
△ 取扱材

# S45C 機械構造用高炭素鋼鋼管

外径 (mm)	肉厚 (mm)	在庫
190.7	11.0	△
	12.0	◎
	15.0	◎
	18.0	◎
	20.0	◎
	23.0	
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	△
	55.0	△
	193.7	15.0
20.0		◎
25.0		◎
200.0	15.0	○
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	△
55.0	△	
203.0	40.0	△
205.0	15.0	◎
	16.0	○
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	○

外径 (mm)	肉厚 (mm)	在庫
210.0	25.0	○
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	○
	50.0	△
	55.0	△
216.3	15.0	◎
	18.0	◎
	18.2	
	20.0	◎
	22.0	△
	23.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
50.0	◎	
55.0		
219.1	12.0	○
	15.0	◎
	18.0	
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
50.0	◎	
232.0	15.0	◎
	16.0	
	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎

外径 (mm)	肉厚 (mm)	在庫
232.0	35.0	◎
	40.0	◎
	45.0	◎
	48.0	△
	50.0	◎
	55.0	△
241.8	15.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
50.0	◎	
55.0	○	
60.0	○	
244.5	15.0	◎
	20.0	◎
	24.0	△
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	◎
	55.0	○
60.0	○	

◎ 常備材  
○ 非常備材  
△ 取扱材

# S45C

## 機械構造用高炭素鋼鋼管

外径 (mm)	肉厚 (mm)	在庫
250.0	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	◎
	55.0	○
254.0	15.0	○
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	◎
	55.0	○
257.0	50.0	
	55.0	
	60.0	
	65.0	
260.0	30.0	◎
	35.0	◎
	40.0	◎
	45.0	○
267.4	15.0	○
	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	◎
	55.0	○
60.0		

外径 (mm)	肉厚 (mm)	在庫
273.1	10.0	
	15.0	◎
	20.0	◎
	25.0	◎
	26.0	△
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	◎
	55.0	△
	60.0	
280.0	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	○
285.0	20.0	△
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	○
298.5	15.0	◎
	20.0	◎
	25.0	◎
	28.0	○
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	◎
	54.0	○
	55.0	◎
60.0	○	

外径 (mm)	肉厚 (mm)	在庫
302.0	50.0	
	55.0	
	60.0	
	65.0	
	70.0	
305.0	15.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	38.0	
	40.0	◎
	45.0	◎
	50.0	◎
	318.5	15.0
17.0		
18.0		△
20.0		◎
25.0		◎
30.0		◎
33.0		
34.0		
35.0		◎
38.0		
40.0	◎	
45.0	◎	
50.0	◎	
55.0	◎	
60.0	○	
65.0	○	
323.9	18.0	◎
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎

◎ 常備材  
○ 非常備材  
△ 取扱材

# S45C 機械構造用高炭素鋼鋼管

外径 (mm)	肉厚 (mm)	在庫
323.9	40.0	◎
	45.0	◎
	50.0	◎
	55.0	△
	60.0	△
	65.0	△
339.7	15.0	△
	18.0	
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	◎
	55.0	◎
	60.0	
	65.0	
355.6	12.0	○
	15.0	
	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	◎
	55.0	◎
	60.0	◎
	63.0	
	65.0	△
365.0	20.0	
	25.0	○
	30.0	○
	35.0	○
	40.0	○
	45.0	○
	50.0	○

外径 (mm)	肉厚 (mm)	在庫
365.1	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	50.0	◎
	55.0	◎
	60.0	◎
	65.0	◎
368.0	40.0	△
381.0	20.0	◎
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
406.4	20.0	○
	25.0	◎
	30.0	◎
	35.0	◎
	40.0	◎
	45.0	◎
	48.0	△
	50.0	◎
	55.0	○
	60.0	△
80.0		
426.0	15.0	
	25.0	○
	30.0	△
	35.0	
	50.0	◎

- ◎ 常備材
- 非常備材
- △ 取扱材